1 Second Testing

- · QUICK
- · SIMPLE
- · ACCURATE

4 IN 1

- · BODY TEMPERATURE
- · SURFACE TEMPERATURE
- · HIGH TEMPERATURE ALARM
- · MEMORIZE 32 TEST DATA

TECHNICAL SPECIFICATIONS

1. Normal using condition:
Ambient temperature:10℃~40℃ (50℉~104℉)
Relative humidity:≤85%

2. Batteries: DC 3V (2 pcs AA batteries)

3. Unit size: 155 x 100 x 40 mm (L x W x H)

4. Unit weight (without battery): 105g

5. Temperature display resolution: 0.1℃ (0.1℉)

6. Measuring range:

In body mode: 32.0℃~43.0℃ (89.6℉~109.4℉)
        Under body mode, there is three color backlits:
        Green color backlit:
        ≤37.3℃ (99.1℉), means normal temperature.
        Orange color backlit:
        37.4℃~37.9℃ (99.3℉~100.2℉), means low fever.
        Red color backlit:
        ≥38℃ (100.4℉), means high fever.

In surface temp mode: 0℃~60℃ (32℉~140℉)

In room mode: 0℃~40℃(32℉~104℉)

7. Precision:
32.0℃~34.9℃ (89.6℉~94.8℉) ±0.3℃(±0.6℉)
35.0℃~42.0℃ (95℉~107.6℉)   ±0.2℃(±0.4℉)
42.1℃~43.0℃ (107.8℉~109.4℉) ±0.3℃(±0.6℉)

8. Consumption: ≤300mW

9. Accuracy: ±0.3℃ (0.6℉)

10. Measuring distance: 3cm ~ 5cm (1.2in ~ 2in)

11. Automatic power-off: <30 secs

12. Memory: 32 sets

13. Measuring position: Forehead skin

Berrcom®

Please read the product manual carefully or purchase and use under the guidance of medical staff
For details on contraindications or precautions